

SPEED

全新设计

伺服驱动节能高速
注塑机系列

技术参数 (128-468吨)

超高速

高精度

高响应

202307

震雄集团

地址: 香港威非路万国宝通中心20楼2001室 广东省深圳市坪山区坑梓街道震雄工业园
广东省佛山市顺德区大良红岗工业区 浙江省宁波市北仑区大港工业城甬江路28号
电话: 400 930 0026 (0755) 8413 9999
官网: www.chenhsong.com



企业公众号



企业官网










企业抖音号

扫一扫
探索更多








技术参数

		SPEED128		SPEED168		SPEED208		SPEED258		SPEED328		SPEED398		SPEED468	
		A	B	A	B	A	B	A	B	A	B	A	B	A	B
射胶部份															
螺杆直径	mm	31	36	36	41	41	46	41	46	46	52	60	67	60	67
螺杆长径比	L/D	24.4	21	23.9	21	23.6	21	23.6	21	23.7	21	23.5	21	23.5	21
螺杆行程	mm	180		205		230		230		260		335		335	
射胶容积	cm ³	136	183	209	271	304	382	304	382	432	552	947	1181	947	1181
射胶量(PS)	g	124	167	190	246	276	348	276	348	393	502	862	1075	862	1075
	oz	4.4	5.9	6.7	8.7	9.7	12.3	9.7	12.3	13.9	17.7	30.4	37.9	30.4	37.9
射胶压力(最大)	kgf/cm ²	2548	1890	2451	1890	2119	1683	2119	1683	2419	1893	1867	1497	1867	1497
射胶速率	cm ³ /s	226	305	305	396	396	499	396	499	499	637	848	1058	848	1058
射胶速度	mm/s	300		300		300		300		300		300		300	
螺杆转速(最大)	rpm	300		300		300		300		300		300		300	
射咀推力(最大)	t	4.2		4.2		6.2		6.2		6.2		9.1		9.1	
射咀行程	mm	275		290		330		330		380		440		440	
锁模部份															
锁模力(最大)	t	128		168		208		258		328		398		468	
开模行程	mm	380		450		510		560		660		720		820	
导柱内距(水平*垂直)	mm	410x410		470x470		530x530		580x580		680x680		730x730		830x830	
容模量(最薄-最厚)	mm	150-450		170-520		180-550		190-580		225-680		250-730		300-850	
顶针推力	t	3.4		4.2		6.7		6.7		11.1		11.1		16.6	
顶针行程	mm	120		140		150		150		180		215		220	
定位法兰	mm	125		125		160		160		160		160		200	
电力/电热															
系统压力	kgf/cm ²	175		175		175		175		175		175		175	
油泵电机功率	kW	34		40		40		40		40+34		40+40		40+40	
电热量	kW	10.5		13.2		16.5		16.5		21.3		33.8		33.8	
温度控制区		3+1		3+1		3+1		3+1		3+1		4+1		4+1	
其它															
机身尺寸(长*宽*高)	m	4.82x1.27x1.83		5.18x1.29x1.89		5.79x1.5x1.97		5.98x1.58x2.01		7.14x1.78x2.09		7.97x1.93x2.28		8.72x2.03x2.24	
油箱容积	L	200		250		330		330		580		760		850	
机重(约)	t	4		4.94		6.8		7.8		13.2		16.7		19.8	

码模孔



T型槽加码模孔(选配)



*以上技术参数仅供参考，在不同情况下可能出现偏差。本公司不断进行产品提升，故保留更改产品规格与参数而不另行通知的权利，本规格表的最终解释权归本公司所有。